

YOUNG Barometric Pressure Sensors combine high accuracy and low power over a wide range of pressures and temperatures.

Model 61302V provides a calibrated 0-5 VDC analog output. Analog current consumption is less than 3 mA. A special "sleep" mode further reduces current to about 1 μ A. RS232 serial output is also available in the standard sensor.

Model 61302L features a standard 4-20 mA analog output. Two serial options, RS-232 and RS-485, are included with this model.

The compact size of the barometer allows easy placement in most standard instrument enclosures. A plug-in connector simplifies wiring.

For outdoor use, an optional **Weatherproof Enclosure** offers a convenient mounting location while the **Pressure Port** helps minimize dynamic pressure errors due to wind.



Specifications

Pressure Range:	500 to 1100 hPa
Operating Temperature:	-40 to +60°C
Digital Accuracy*	0.2 hPa (25°C) 0.3 hPa (-40 to +60°C)
Analog Accuracy**	0.05% of analog pressure range
Analog Temperature Dependence	0.0017% of analog pressure range/ °C (25°C reference)
Long Term Stability:	0.2% FS per year
Update Rate:	1.8 Hz max
Serial Output:	Full duplex RS-232 9600 baud Polled or continuous ASCII text, NMEA Half duplex RS-485 (61302L only)
Analog Output:	0 to 5000 mV, 0 to 2500 mV (61302V) 4 to 20 mA (61302L)
Resolution:	Serial 0.01 hPa Analog 0.025% of analog scale
Power:	7 to 30 VDC 61302V – Vout, 2.8 mA – Sleep mode, 1.4 μ A – RS-232, 7 mA 61302L – 4-20 mA, 25 mA max – RS-232 or RS-485, 7 mA

Dimensions:	90 mm (3.6 in) x 60 mm (2.4 in) x 20 mm (0.8 in)
Weight:	44 g (1.5 oz)

* Defined as ± 1 standard deviation from NIST traceable pressure reference. Includes non-linearity, hysteresis, repeatability, and calibration uncertainty.
 ** Defined as ± 1 standard deviation from ideal analog output. Total analog output accuracy is the root sum square of digital accuracy, analog accuracy, and analog temperature dependence.



Weatherproof Enclosure and Pressure Port

Ordering Information

MODEL

BAROMETRIC PRESSURE SENSOR – 0-5 VDC.....	61302V
BAROMETRIC PRESSURE SENSOR – 4-20 mA	61302L
WEATHERPROOF ENCLOSURE	61360
PRESSURE PORT WITH OFFSET BRACKET.....	61002

CE Complies with applicable CE directives.
 Specifications subject to change without notice.



R. M. YOUNG COMPANY
 2801 Aero Park Drive
 Traverse City, Michigan 49686 USA
 TEL: (231) 946-3980 FAX: (231) 946-4772
 E-mail: met.sales@youngusa.com
 Web Site: www.youngusa.com