





Order form  
Purchaser

Valid from March 2020  
Order no.

## HMT130 Temperature Transmitter

		1	2	3	4	5	6	7	8	9	10	11	12	13	14	Price
Vaisala HUMICAP® Temperature Transmitter		HMT130	T					A	0							
Output parameters		Temperature output only														
Transmitter type	Wall mount/fixe probe							A								
	<i>Remote probe with 3 m cable</i>							B								
	<i>Remote probe with 5 m cable</i>							C								
	<i>Remote probe with 10 m cable</i>							D								
	<i>Remote probe with 10 m cable + 10 m extension</i>							E								
	<i>Remote probe with 20 m cable</i>							F								
	<i>Remote probe with 1.2 m cable</i>							G								
Display	No display								0							
	<i>Display</i>								1							
	<i>No Display, no logo</i>								N							
Analog output signal (RS485 also included)	0...1 V															
	<b>0...5 V</b>															
	<b>0...10 V</b>															
SPECIAL	Define scale:															
Parameter for Output 1	T															
	<i>-40...+60 °C (-40...+140 °F)</i>															
	<i>-20...+80 °C (-4...+176 °F)</i>															
	<b>0...+60 °C (+32...+140 °F)</b>															
	<i>-40...+80 °C (-40...+176 °F)</i>															
	<b>0...+50 °C (+32...+122 °F)</b>															
SPECIAL	Define quantity															
Parameter for Output 2	None															
Display Units	Metric															
	<b>Non metric</b>															
Sensor protection	Plastic grid															
	<b>Plastic grid with PTFE filter</b>															
	<i>Stainless steel sintered filter (for remote probes only)</i>															
	<i>Teflon sintered filter for HMP110 DRW244938SP</i>															
Transmitter installation	No accessories															
	<i>Rain shield with installation kit (215109)</i>															
Installation kit for probe	No accessories															
	<i>Duct installation kit (215619)</i>															
	<i>Probe mounting flange (226061)</i>															
	<i>Outdoor installation: DTR504A Radiation Shield with probe installation kit (DTR504A)</i>															
	<i>Probe mounting clamp, 1 piece (225501)</i>															
Cable bushings	<b>Cable gland for 2...6 mm diameter cable</b>															
	<i>Conduit fitting PG9</i>															
	<i>Conduit fitting NPT 1/2"</i>															
	<b>No bushing (rubber plug)</b>															
	<i>All bushings (includes A, B, C and D)</i>															
PC Accessories	No															
	<i>Service cable for PC, USB (219685)</i>															
Operation manual	No manual															
	<b>Multilingual</b>															
															Total	
															QTY	
															Total value	

\*) Voltage output value between 0...10 V

Selections in bold are included in the prices of the basic versions  
Selections in italic are available at an extra cost

Example of order code with typical settings

HMT130 T A 1 D B A 0 1 A 1 1 A 0 Z